

STAINLESS MOTORS, INC.

7601 Nita Place NE • Rio Rancho • NM • 87144

(505) 867-0224 • Fax: (505) 867-0225

STAINLESS STEEL WASHDOWN DUTY MOTOR DATA SHEET

Date: 06/22/05

RATED HORSEPOWER	$\frac{3}{4}$hp
VOLTAGE / PHASES / FREQUENCY	208-230/460/3/60Hz
FULL LOAD SPEED	1,740 RPM
APPLICABLE NEMA FRAMES	56, 56C
ENCLOSURE TYPE	TEFC
SERVICE FACTOR	1.15
INSULATION CLASS	F
MAXIMUM AMBIENT TEMPERATURE	40°
BEARING SIZE / TYPE (SHAFT END)	6205-2RS
(OPPOSITE SHAFT END)	6204-2RS
NEMA DESIGN LETTER	B
NEMA CODE LETTER	L
FULL LOAD CURRENT	2.3-2.2/1.1 AMPS
NOMINAL FULL LOAD EFFICIENCY	82.5%
SUITABLE FOR USE WITH VARIABLE FREQUENCY DRIVE (4:1 RATIO)	YES

HP/SF RATING CRITERIA WITH LINE VOLTAGE INPUT

VOLTAGE VARIATION	LESS THAN $\pm 10\%$
PHASE VOLTAGE IMBALANCE (60HZ LINE)	LESS THAN $\pm 1\%$
FREQUENCY VARIATION	LESS THAN $\pm 5\%$
TEMPERATURE RANGE	BETWEEN -15° AND 40° C
MAXIMUM ALTITUDE WITHOUT DERATING	LESS THAN 3,300 Ft.

COMMENTS: CLASS F THERMOSTATS